



Safety Data Sheet

The Dow Chemical Company

Product Name: CARBOWAX(TM) POLYETHYLENE GLYCOL 600

Revision Date: 2007/12/12

Print Date: 28 Apr 2011

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Identification of the substance/preparation and of the company/undertaking

Product Name

CARBOWAX(TM) POLYETHYLENE GLYCOL 600

Use of the substance/preparation

A partial list of examples include pharmaceutical products, personal care products, automotive products, household products, packaging products, petroleum chemicals, plastics, inks, coatings, adhesives, chemical intermediates, rubber processing, lubricants, metalworking fluids, mold release agents, ceramics, and wood treating. CAUTION! For food, feed, drug or cosmetic applications, use CARBOWAX(TM) SENTRY(TM) brands, NF (National Formulary), FCC (Food Chemical Codex) Grade. Only SENTRY brand products are tested to meet NF and FCC standards for these applications.

COMPANY IDENTIFICATION

The Dow Chemical Company
2030 Willard H. Dow Center
48674 Midland, MI
USA

Customer Information Number: 800-258-2436

For questions about this SDS, contact: SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 989-636-4400

Local Emergency Contact: 00 31 115 69 4982

2. Hazards Identification

This product is not classified as dangerous according to EC criteria.

3. Composition/information on ingredients

Component	Amount	Classification:	CAS #	EC #
Polyethylene glycol#	> 99.0 %	Not classified.	25322-68-3	Polymer

Substance(s) with an Occupational Exposure Limit.

®(TM)*Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

4. First-aid measures

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Skin Contact: Wash skin with plenty of water.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Ingestion: No emergency medical treatment necessary.

Notes to Physician: Absorption may be promoted by damaged skin. J Pharm Sci. 1985 Oct;74(10):1062-6; Burns Incl Therm Inj 1982 Sep;9(1):49-52. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Storage

Store in original container. Use product promptly after opening. Avoid prolonged exposure to heat and air. Store in the following material(s): Stainless steel. Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Plasite 3066 lined container. Plasite 3070 lined container. 316 stainless steel.

8. Exposure Controls / Personal Protection

Exposure Limits

Component	List	Type	Value
Polyethylene glycol	WEEL	TWA Particulate.	10 mg/m3

Personal Protection

Eye/Face Protection: Use safety glasses. Safety glasses should be consistent with EN 166 or equivalent.

Skin Protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

9. Physical and Chemical Properties

Physical State	Liquid above freezing point
Color	Colorless above freezing point
Odor	Mild

Flash Point - Closed Cup	238 °C <i>ASTM D93</i>
Flash Point - Open Cup	273 °C <i>ASTM D92</i>
Flammable Limits In Air	Lower: No test data available Upper: No test data available
Autoignition Temperature	No test data available
Vapor Pressure	< 0.01 mmHg @ 20 °C <i>ASTM E1719</i>
Boiling Point (760 mmHg)	> 200 °C <i>Calculated</i> Decomposes.
Vapor Density (air = 1)	>10 <i>Calculated</i>
Specific Gravity (H2O = 1)	1.128 20 °C/20 °C <i>Calculated</i>
Liquid Density	1.3 g/cm ³ @ 20 °C <i>ASTM D4052</i>
Freezing Point	20 - 25 °C <i>ASTM D1177</i>
Melting Point	Not applicable to liquids
Solubility in Water (by weight)	100 % @ 20 °C <i>Measured</i>
pH	4.5 - 7.0 <i>ASTM E70</i> (5% aqueous solution)
Molecular Weight	570 - 630 g/mol <i>Calculated</i>
Octanol/Water Partition Coefficient	< 2.25 <i>Estimated</i>
Kinematic Viscosity	9.9 - 11.3 mm ² /s @ 98.9 °C <i>ASTM D445</i>

10. Stability and Reactivity

Stability/Instability

Thermally stable at typical use temperatures.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous Polymerization

Will not occur.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Carbon dioxide. Carboxylic acids. Polymer fragments.

11. Toxicological Information

Acute Toxicity

Ingestion

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, Rat > 30,000 mg/kg

Eye Contact

May cause slight temporary eye irritation. Corneal injury is unlikely.

Skin Contact

Prolonged contact may cause slight skin irritation with local redness.

Skin Absorption

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Prolonged/repeated exposure to damaged skin (as in burn patients) may result in absorption of toxic amounts.

LD50, Rabbit > 20,000 mg/kg

Inhalation

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

Maximum attainable concentration. LC50, 8 h, Vapor, Rat > 13 ppm

Sensitization

Skin

A similar material did not cause allergic skin reactions when tested in humans.

Repeated Dose Toxicity

Recent findings of kidney failure and death in burn patients, as well as some studies using animal burn models, suggest that polyethylene glycol may have been a factor. The use of topical applications containing this material may not be appropriate in severely burned patients or individuals with impaired renal function. Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Chronic Toxicity and Carcinogenicity

Similar material(s) did not cause cancer in laboratory animals.

Developmental Toxicity

For similar material(s): Did not cause birth defects in laboratory animals.

Reproductive Toxicity

For similar material(s): In animal studies, did not interfere with reproduction.

Genetic Toxicology

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. Ecological Information

CHEMICAL FATE

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). No bioconcentration is expected because of the relatively high water solubility.

Partition coefficient, n-octanol/water (log Pow): < 2.25 Estimated

Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
90 %		OECD 301F Test
55 %		OECD 306 Test

ECOTOXICITY

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50 greater than 100 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (*Pimephales promelas*): > 10,000 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea *Daphnia magna*: > 10,000 mg/l

Aquatic Plant Toxicity

EC50, diatom *Skeletonema costatum*, biomass growth inhibition, 3 d: 14,853 mg/l

13. Disposal Considerations

Any disposal practice must be in compliance with all local and national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water.

14. Transport Information

ROAD & RAIL

NOT REGULATED

OCEAN
NOT REGULATED

AIR
NOT REGULATED

INLAND WATERWAYS
NOT REGULATED

15. Regulatory Information

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

European Inventory of Existing Commercial Chemical Substances (EINECS)

This product is a polymer according to the definition in Directive 92/32/EEC (7th Amendment to Directive 67/548/EEC) and all of its starting materials and intentional additives are listed in the European Inventory of Existing Commercial Chemical Substances (EINECS) or in compliance with European (EU) chemical inventory requirements.

EC Classification and User Label Information

This product is not classified as dangerous according to EC criteria.

Safety data sheet available for professional users on request.

16. Other Information

Product Literature

Additional information on this product may be obtained by calling your Dow Chemical Company sales or customer service contact. Ask for a product brochure. Additional information on this and other Dow products may be obtained by visiting our web page at www.dow.com.

Revision

Identification Number: 78091 / 0000 / Issue Date 2007/12/12 / Version: 2.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

